

		1.2 Petrol DIG TURBO		1.6 Petrol		1.5 Diesel		1.6 Diesel			
MODEL											
Seating capacity		persons	5								
ENGINE											
No. of cylinders, configuration			4, in line	4, in line	4, in line	4, in line	4, in line				
Valves per cylinder			4	4	4	2	4				
Engine capacity		cm ³	1197	1197	1618	1461	1598				
Bore x stroke		mm	72.2 x 73.1	72.2 x 73.1	79.7x81.1	76 x 80.5	80x79.5				
Max. engine power 1)		kW(PS)/min-1	85 (115)/4500	85 (115)/5200	120 (163)/5600	81 (110)/4000	96 (130)/4000				
Max. torque 1)		Nm/min-1	190/2000	165/1750	240/2000-4000	260/1750-2500	320/1750				
Compression ratio					10.5:1	15.4:1	15.4:1				
Fuel type			Petrol	Petrol	Petrol	Diesel	Diesel				
Fuel tank capacity		litres	55	55	55	55	65	55	65		
DRIVE TRAIN											
		2WD		2WD		2WD		2WD		4WD	
Transmission type			6-speed manual	CVT	6-speed manual	6-speed manual	6-speed manual	CVT	6-speed manual		
Gear ratio	1st		3,727	4,006	3,727	3,727	3,727	2,413	3,727		
	2nd		1,947	↑	2,105	1,947	2,043	↑	2,043		
	3rd		1,323	↓	1,323	1,226	1,323	↓	1,323		
	4th		0,975		0,975	0,838	0,947		0,947		
	5th		0,763		0,763	0,652	0,723		0,723		
	6th		0,638	0,550	0,638	0,560	0,596	0,383	0,596		
	Reverse		3,687	3,771	3,687	3,687	3,641	1,798	3,641		
	Final Drive		4,214	3,517	4,214	4,125	4,133	5,577	4,266		
Driven wheels			2WD	2WD	2WD	2WD	2WD	2WD	All Mode 4x4 / 2WD		
Nissan Stop/Start system			YES	YES	YES	YES	YES	YES	YES		
CHASSIS											
Suspension	front		McPherson Strut with Rigid Mounting Mini sub frame			McPherson Strut with Rigid Mounting Mini sub frame					
	rear		Torsion Beam	Torsion Beam	Torsion Beam	Torsion Beam	Independent Multi-Link	Torsion Beam	Independent Multi-Link		
Steering			Rack and Pinion, power assisted								
Braking system			Discs front and rear, power assisted, ABS incl EBD and Brake Assist								
Wheel size (option)			16" Steel, 17", 18" & 19" Alloy wheel								
Tyre size (option)			215/65R16, 215/60R17, 225/45R19, 215/55R18								
WEIGHTS & DIMENSIONS											
		Torsion Beam		Torsion Beam		Multi-Link		Independent Multi-Link			
Kerb weight min./max. 2)		kg	1331-1456	1343-1469	1369-1494	1379-1507	1429-1557	1465 - 1557	1527-1614		
Gross Vehicle Weight		kg	1860	1880	1880	1910	1960	2005	2030		
Max. payload 2)		kg	529	537	531	531	495	498	503		
Max. axle weight (PAW)	front	kg	1015		1015			1110	1110		
	rear	kg	970	980	960	970			1005		
Max. trailer weight	braked	kg	1200	1000	1500	1350	1800	1400	1800		
	unbraked	kg	675	680	695	692	720	740	750		
Max. vert. load on coupling point		kg	100	100	100	100	100	100	100		
Towing capacity		kg	1200	1000	1500	1350	1800	1400	1800		
Overall length		mm	1806								
Overall width		mm	1806								
Overall height		mm	1590	1590	1590	1590	1595	1590	1595		
Wheelbase		mm	2646								
Track (Unladen)	front	mm	1565								
	rear	mm	1560								
Min. turning circle (kerb to kerb)		m	10,72								
PERFORMANCE											
		6-speed manual		CVT		6-speed manual		6-speed manual		CVT	6-speed manual
Fuel consumption 3)	Urban cycle l/100 km / mpg	16", 17", 18" & 19"	6.6 / 42.8	6.5 / 43.5	7.4 / 38.2	4.2 / 67.3	5.1 / 55.4	5.3 / 53.3	5.7 / 49.6		
	Extra-urban l/100 km / mpg	16", 17", 18" & 19"	5.1 / 55.4	5.2 / 54.3	4.8 / 58.9	3.6 / 78.5	4.1 / 68.9	4.4 / 64.2	4.5 / 62.8		
	Combined l/100 km / mpg	16", 17", 18" & 19"	5.6 / 50.4	5.6 / 50.4	5.8 / 48.7	3.8 / 74.3	4.4 / 64.2	4.7 / 60.1	4.9 / 57.6		
CO2 mass emission (combined)	g/km	16", 17", 18" & 19"	129	129	134	99	116	122	129		
Nox (including DF)	mg/km	16", 17", 18" & 19"	23,8	18,2	9,28	22,91	32,50	15,01	26,78		
THC + Nox (including DF)	mg/km	16", 17", 18" & 19"	70	77,6	-	39,57	68,43	26,63	45,95		
Particles (PM)	mg/km	16", 17", 18" & 19"	0,5	1,85	1,4	0,3	0,098	0,0052	0,463		
Particles (#/km)		16", 17", 18" & 19"	5,76E+11	3,96E+15	6E+11	6,56E+10	4,06E+10	3,66E+10	3,37E+10		
Emission Level			EURO6b	EURO6b	EURO6b	EURO6b	EURO6b	EURO6b	EURO6b		
Max. speed	km/h / mph		185 / 115	173 / 108	200 / 124	182 / 113	190 / 118	183 / 114	190 / 118		
Acceleration 0 - 100 km/h	sec		10,6	12,9	8,9	11,9	9,9	11,1	10,5		
Maintenance Service											

1) In accordance with 715/2007/EC.

2) Figures according model/spec adjustment. Mass is minimum in homologation document. Kerb weight condition is without driver and including coolant, oils, fuel, spare wheel and tools. Payload will be reduced depending on the options and/or accessories installed.

3) In accordance with 715/2007/EC. (Optional equipment, maintenance, driving behaviour, road and weather conditions may affect the official results)